

Clearance & Mounting Requirements

Door Style	Hardware size	Headroom Required	Track curve radius	Jamb Details			
				A	B	C	D
Standard Lift	2" (51)	13" (330) to 19-1/2" (495)	12" (305) or 16" (406)	1-1/2" (38)	3-1/2" (89)	1" (25)	5" (127)
	3" (76)	18" (457), 19" (482) or 21" (533)	16" (406)	2" (51)	4" (102)	1" (25)	6" (152)
Hi-Lift	2" (51)	H.L. + 7-1/2" (191) to H.L. + 10" (254)	16" (406)	1-1/2" (38)	3-1/2" (89)	1" (25)	5" (127)
	3" (76)	H.L. + 9-1/2" (241) to H.L. + 18-1/2" (470)	16" (406)	2" (51)	4" (102)	1" (25)	6" (152)
Vertical Lift	2" (51)	D.H. + 22" (559)	-	1-1/2" (38)	3-1/2" (89)	1" (25)	5" (127)
	3" (76)	D.H. + [22" (559) to 27-1/2" (699)]	-	2" (51)	4" (102)	1" (25)	6" (152)
Low Headroom Front Springs	2" (51)	11" (279) to 11-3/4" (298)	-	1-1/2" (38)	3-1/2" (89)	1" (25)	5" (127)
	3" (76)	13" (330) to 15-1/2" (394)	-	2" (51)	4" (102)	1" (25)	6" (152)
Low Headroom Rear Springs	2" (51)	5" (127) to 5-1/2" (140)	-	1-1/2" (38)	3-1/2" (89)	1" (25)	5" (127)
	3" (76)	7-1/2" (191)	-	2" (51)	4" (102)	1" (25)	6" (152)
Low Headroom Vertical Lift	2" (51)	D.H. + 10" (254) or D.H. + 4" (102)	-	1-1/2" (38)	3-1/2" (89)	1" (25)	5" (127)
	3" (76)	D.H. + 10" (254) or D.H. + 4" (102)	-	2" (51)	4" (102)	1" (25)	6" (152)

