## Thermospan<sup>®</sup> 150

	Headroom***		Sideroom**		Depth Into Room	Center Line of Springs	
Туре	2" Track	3" Track	2" Track	3" Track	2" & 3" Track	2" Track	3" Track
Standard Lift Manual 12"R	13"- 17"	NA	4.5"	5.5"	Opening Height +18"	Opening Height +12"	NA
Standard Lift Manual 15"R	15"- 20"	16"- 21"				Opening Height +13"	Opening Height +14"
Standard Lift Motor Oper.12"R	15"- 20"	NA			Opening Height +66"	Opening Height +12"	NA
Standard Lift Motor Oper.15"R	15"- 20"	18"- 24"				Opening Height +13"	Opening Height +14"
High Lift Manual	High Lift +12"					Opening Height	
High Lift Motor Oper.			24" One Side		Opening Height –Lift +30"	Opening Height +Lift +6.5"	+Lift +7.5"
Vertical Lift Manual	Door Height +20"		4.5"	5.5"		Double Door Height +13"	
Vertical Lift Motor Oper.			24" One Side		18"		
Low Headroom Manual*	6"-15"	6"-15"	6"	9"	Opening Height +20" to 26"		Acet
Low Headroom Motor Oper.*	9"-17"	9"-17"			Opening Height +66"	Does Not Apply	

\*Note: Springs must be rear mount to achieve minimum headroom listed. Front mount torsion headroom depends on drum size, and varies over the range listed. See Approval Drawing.

\*\*Note: 8" sideroom required, one side, for doors with chain hoist.

\*\*\*Note: Headroom for standard lift depends on drum size, and varies over the range listed. See Approval Drawing.



## **Wayne Dalton Commercial Sectional Doors**



**Standard Lift** 




High Lift (break-away standard; no break-away available)



Roof Pitch (standard or high lift)



Vertical Lift (break-away standard; no break-away available)



Low Headroom (rear mount torsion)



Low Headroom (front mount torsion)