# insulated rolling door THERMISER®

Model ESD20



# MAINTAIN TEMPERATURES AND REDUCE SOUND TRANSMISSION

### **ENERGY-EFFICIENT CLIMATE CONTROL**

Thermiser Insulated Rolling Doors, designed for exterior use, help maintain different temperatures on each side of the door. They are an ideal choice for use in environments that require climate control, security and durability: distribution, industrial, hospitality, retail and more.

#### **MORE REASONS TO LOVE THERMISER**

Thermiser doors store compactly, require little to no maintenance and deliver a low life cycle cost. In fact, we warranty this product for 50,000 cycles as standard.

### **SEAL THE BUILDING ENVELOPE**

Foamed in place insulation offers superior protection against the elements, improved security and reduced sound transmission. The Thermiser helps seal the building envelope and keeps noise in - or out.

#### **REDUCES SOUND TRANSMISSION**


Sound Transmission Class (STC) rating is up to 32 for the entire assembly. All configurations are evaluated per ASTM E90, based on testing a complete, operable assembly.



# ALL-RITE DOCK & DOOR SYSTEMS INC.

4 Baker Road, Brampton, Ontario Canada T: 905-840-4848 E: info@all-ritedoors.com

# STANDARD COMPONENT MATERIALS AND FINISHES



**BRACKETS** - Steel with powder coating to match curtin. Bolt to guide assembly and support counter-balance shaft and curtain.

**COUNTER-BALANCE SHAFT** - Steel. Supports curtain and contains torsion springs for assisting operation.

**HOOD** - Galvanized steel with GalvaNex<sup>™</sup> polyester enamel finish to match curtain. Encloses the curtain and provides weather resistance at the head of the door.

**CURTAIN** - Galvanized steel with GalvaNex<sup>™</sup> polyester enamel finish in Gray, Tan, White or Brown. Flame Spread Index of 0 and a Smoke Developed Index of 10 as tested per ASTM E84. The slat has an R-value of 8.0 as calculated using the ASHRAE Handbook of Fundamentals.

**GUIDES** - Structural steel with powder coating to match curtain. Angle assemblies bolt to the wall and support the weight of the door.

**BOTTOM BAR** - If width is less than 24'5", extruded aluminum supplied in mill finish. If width is greater than 24'5", steel supplied with powder coating to match curtain.

## OPERATION AND STRUCTURAL REQUIREMENTS

# Hand chain, hand crank and a variety of motor options are available.

All of our rolling products are supported by the guides. There is no additional support required unless hood supports are mandated by a larger opening width.

### **OPTIONAL MATERIALS AND FINISHES**

- ► Aluminum in mill, clear and color anodized
- ► Stainless steel 300 series in #4 finish
- ► SpectraShield<sup>®</sup> Powder Coating in more than 180 colors

#### Brackets, Guides and Bottom Bar

- Hot-dip galvanizing on steel components
- ► Zinc-enriched, corrosion-resistant powder coating in Gray



## **CUSTOM-DESIGNED SOLUTIONS**

Contact our experienced Architectural Design Support Team for help in customizing our products to fit your specific application. Call 800.294.4358 ext. 1280 • ads@cooksondoor.com



# ALL-RITE DOCK & DOOR SYSTEMS INC.

4 Baker Road, Brampton, Ontario Canada T: 905-840-4848 E: info@all-ritedoors.com